



Recycle with Asphalt Rubber



Due to the superior performance of Asphalt Rubber Caltrans and many California Agencies have adopted a reduced thickness design guideline of 50% for reflective cracking compared to conventional asphalt hot mix. This reduction in overlay thickness makes Asphalt Rubber significantly cheaper than conventional asphalt.

Caltrans 50% Reduced Thickness Design Guideline

- Caltrans developed the guidelines in 1992
- Since 1992 Caltrans has recycled over **20 Million Tires** based on this guide line
- **YOUR AGENCY CAN DO THE SAME THING**

Caltrans Equivalencies for Field Blended RAC

(Thickness in feet)

DGAC (Dense Graded)	RAC Type G (Asphalt Rubber Gap Graded Mixes)
0.15'	0.10'
0.20'	0.10'

Asphalt Rubber: Over 50 years of recycling through responsible design

Our Asphalt Rubber Binders meet AB338 and **CalRecycle**  grant requirements



2006.02

FNF—with over 20 years of experience in the Industry

We can assist you with your design. Call us at 949-295-7503 for a free consultation



www.FNFinc.com

- info@fnfinc.com

CALIFORNIA:

P.O. Box 5236 - Fullerton, CA 92838
Phone (949) 295-7503

ARIZONA:

115 South 48th Street, Tempe, AZ 85281
Phone: 480.784.2910 | Fax: 480.829.8607

